

MSDS **Material Safety Data Sheet**

Wilsonart International



MSDS Number: 18950
Page 1 of 5

Wilsonart® 3000 Series Adhesives

Revision Date: 08/20/09
Revision No: 5

1 **PRODUCT AND COMPANY IDENTIFICATION**

Common Name: Wilsonart® 3000 Series Adhesive
Includes: Wilsonart® 3000 Adhesive
Wilsonart® 3001 Adhesive
Wilsonart® 3002 Adhesive
Wilsonart® 3028 Adhesive
Wilsonart® 3029 Adhesive
Wilsonart® 3031 Adhesive
Wilsonart® 3050 Adhesive

Manufacturer: WILSONART INTERNATIONAL, INC.
P. O. BOX 6110 – 2400 WILSON PLACE
TEMPLE, TX 76503
INFORMATION PHONE: 800-433-3222 (USA)

Trade Name: WA 3000 Series Adhesive

Material Uses: Adhesive for laminate

In Case of Emergency Contact CHEMTREC: 800-424-9300 (USA)
703-527-3887 (INTERNATIONAL)

2 **HAZARDS IDENTIFICATION**

Route of Entry: Skin, eyes, inhalation, ingestion.

Target Organs: None.

Skin Contact: May cause skin irritation.


Eye Contact: May cause eye irritation.

Inhalation: Breathing vapors may cause irritation to the respiratory tract.

Ingestion: Not an expected route of entry. If ingested it may cause irritation to the gastro-intestinal tract.

HMIS (United States):	
HEALTH	1
FLAMMABILITY	1
REACTIVITY	0
PPE	B

NFPA (United States):



WHMIS (Canada): D2A



3 **COMPOSITION/INFORMATION ON INGREDIENTS**

Name	CAS#	% by Weight
Vinyl Acetate Polymers	Not Applicable	30 – 60
Aliphatic Ester (3001)	NJT SRN 950003	5 – 30
Aromatic Diester (3000, 3002, 3050)	NJT SRN 950001; RN7415*	5 – 30
Aromatic Diester (3028)	NJT SRN 970004	1 – 5

* See Section 15 for Canadian HMIRC Registry Number exemptions

4 FIRST AID MEASURES

Skin Contact: Remove contaminated clothing and wash affected areas with soap and water. If irritation develops, seek medical attention.

Eye Contact: Flush eyes with water for 15 minutes. Remove contact lenses prior to water flush. Seek medical attention.

Inhalation: Remove patient to fresh air. If patient is having difficulty breathing, seek immediate medical attention. If not breathing, clear airway and start mouth-to-mouth artificial respiration (or use bag-mask respirator). Seek immediate medical attention.

Ingestion: DO NOT induce vomiting. Seek immediate medical attention. DO NOT give anything by mouth to an unconscious person.

5 FIRE FIGHTING MEASURES

Flash Point: Not Applicable.

Flash Point Method: Not Applicable.

Autoignition Temp.: Not Applicable.

Burning Rate: Material is not flammable. Dry adhesive will burn.

Flammability Classification: Not Applicable.

Firefighting Equipment: Use self-contained breathing apparatus (SCBA) with a full-face piece and pressure demand or other positive-pressure mode and protective gear appropriate for surrounding materials. In case of fire, use water, dry chemical, CO₂, or alcohol foam extinguishing media.

Hazardous Products of Combustion: Carbon Oxides (CO and CO₂), Acetic Acid, and various Hydrocarbons.

6 ACCIDENTAL RELEASE MEASURES

Personal Precautions: Wear appropriate PPE. Make sure area is well ventilated. Spilled adhesive may be slippery.

Environmental Precautions: Keep out of sewers and drains.

Clean-up Methods: Dike and contain spill. Absorb spilled product with vermiculite, dry sand, or earth. Place in a suitable non-leaking container and tightly seal for disposal.

7 HANDLING AND STORAGE

Handling Precautions: Wear appropriate PPE. If used indoors, make sure to provide adequate ventilation to prevent vapor build-up. Avoid breathing of vapors.

Storage Requirements: Store in a cool, dry, well-ventilated area. Avoid freezing temperatures. Minimize contact with atmospheric air to prevent inoculation with microorganisms.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Use in a well ventilated area. Ensure that a working eyewash and safety shower are in the work area.

Protective Equipment: Wear safety glasses with side shields, and neoprene or rubber gloves.

Exposure Guidelines / Other:

Product Name	Exposure Limits
NJTSRN 970004	OSHA PEL: TWA 5 mg/m ³
	ACGIH TLV: TWA 5 mg/m ³

Consult local authorities and local regulations for exposure limits.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Liquid – color varies by adhesive grade.

Physical State: Liquid

Odor: Mild sweet

MSDS **Material Safety Data Sheet**

Wilsonart International



MSDS Number: 18950
Page 3 of 5

Wilsonart® 3000 Series Adhesives

Revision Date: 08/20/09
Revision No: 5

Autoignition Temp.: Not Applicable

Boiling Point: Similar to water

Flash Point: Not Applicable

Molecular Weight: Not Applicable

pH: 4 – 5.5

Specific Gravity / Density: 1.08 – 1.10 (~9.1 lb/gal)

Vapor Pressure: Equivalent to water

VHAP: Not Applicable

Composite Partial Pressure: Not Applicable

Freezing / Melting Point: Similar to water

Percent Volatile: Not Available

Solubility: Soluble in Water

Vapor Density: Equivalent to water

Viscosity: 1200 – 4500 Cp

VOC: < 20 g/L

10

STABILITY AND REACTIVITY

Stability: Product is stable as supplied.

Conditions to Avoid: Freezing and boiling temperatures.

Materials to Avoid (incompatibility): Strong acids, strong bases, copper and copper alloys.

Hazardous Decomposition Products: Carbon Oxides (CO and CO₂), Acetic Acid, and various Hydrocarbons.

Hazardous Polymerization: Will not polymerize.

11

TOXICOLOGICAL INFORMATION

Acute Toxicity to Animals:

Aliphatic Ester (NJTSRN 950003):

Inhalation 4 hour LC50 > 1721 mg/m³ (rat).

Oral LD50 > 6400 mg/kg (rat).

Oral LD50 > 3200 mg/kg (mouse).

Dermal LD50 > 23200 mg/kg (guinea pig).

Aromatic Diester (NJTSRN 950001, RN 7415):

Inhalation 4 hour LC50 > 6.7 mg/L (rat).

Oral LD50 = 20400 mg/kg (rat).

Dermal LD50 > 10000 mg/kg (rabbit).

Aromatic Diester (NJTSRN 970004):

Oral LD50 = 8000 mg/kg (rat).

Vinyl Acetate Polymers (Not Applicable):

Oral toxicity LD50 > 2000 mg/kg (rat).

Chronic Toxicity to Animals: A component of this product has been reported to cause lung effects, mild and reversible liver effects, mild and reversible changes in blood cell counts, kidney abnormalities, female reproductive effects, effects on female fertility, and testis damage..

Acute Toxicity to Humans: No additional information.

Chronic Toxicity on Humans: No additional information.

Carcinogenic Effects: No additional information.

Mutagenic Effects: No additional information.

Teratogenic Effects: No additional information.

Developmental Toxicity: A component of this product has been shown to cause birth defects in laboratory animal studies. Relevance to humans is uncertain.

12

ECOLOGICAL INFORMATION

Ecotoxicity: Not Available.

BOD5 and COD: Not Available.

Biodegradable / OECD: Not Available.

Mobility: Not Available.

Toxicity of the Products of Biodegradation: Not Available.

Special Remarks on the Products of Biodegradation: Not Available.

13

DISPOSAL CONSIDERATIONS

Absorb spilled product with vermiculite, dry sand, or earth and allow to solidify. Dispose of solid material in a suitable container.

Dispose of in accordance with Federal, State, and local regulations.

MSDS Material Safety Data Sheet

Wilsonart International



MSDS Number: 18950
Page 4 of 5

Wilsonart® 3000 Series Adhesives

Revision Date: 08/20/09
Revision No: 5

14 TRANSPORT INFORMATION

Restrictions: None known.
DOT Requirements: Not a DOT controlled material (United States).
DOT Classification: Adhesive Resin Compound.
Markings: None.
Packaging Requirements: Keep from freezing.
ADR Requirements: Not an ADR controlled material (Europe).
IMDG Requirements: Not an IMDG controlled material.
IATA Requirements: Not an IATA controlled material.
Marine Pollutant: Not expected to be a marine pollutant.

15 REGULATORY INFORMATION

U.S. Federal Regulations

Chemical (& CAS Number)	SARA 302 (EHS)TPQ	SARA 304 (EHS)Rq	SARA 313 <i>de minimis</i>	CERCLA Rq	CAA 112(r) TQ	RCRA Code
Aromatic Diester (NJTSRN 950001; RN7415*)				100		

All quantities in pounds

State Regulations

Chemical (& CAS Number)	CA Prop 65	MA RTK	MN RTK	NJ RTK	PA RTK	RI RTK
Aromatic Diester (NJTSRN 950001; RN7415*)	X	X		X	X	
Aromatic Diester (NJTSRN 970004)	X	X	X	X	X	X

This product contains substances known to the State of California to cause cancer or reproductive harm.

International Regulations

DSL (Canada): The chemicals in this product are listed.
EINECS: The chemicals in this product are listed.
WHMIS: D2A.
HMIRC Registry Number 7415 was filed on September 2, 2008 with the Canadian Hazardous Materials Information review Commission.

16 OTHER INFORMATION

References

Lewis, R. J., *Rapid Guide to Hazardous Chemicals in the Workplace*, 4th ed., Wiley-Interscience, New York, 2000.
NIOSH Pocket Guide to Chemical Hazards, Department of Health and Human Services, National Institute for Occupational Safety and Health, 2004.
Patty's Toxicology, 5th ed. John Wiley & Sons, Inc. 2001.
TLVs and BEIs, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Agents, ACGIH Worldwide, Cincinnati, 2007.

Glossary

ACGIH – American Conference of Governmental Industrial Hygienists
ASTM – American Society for Testing and Materials
ADR – Agreement on Dangerous Goods by Road (Europe)
BOD5 – Biological Oxygen Demand in 5 days

MSDS *Material Safety Data Sheet*

Wilsonart International



MSDS Number: 18950
Page 5 of 5

Wilsonart® 3000 Series Adhesives

Revision Date: 08/20/09
Revision No: 5

CAA – Clean Air Act
CAS – Chemical Abstracts Services
CEPA – Canadian Environmental Protection Act
CERCLA – Comprehensive Environmental Response, Compensations, and Liability Act
CFR – Code of Federal Regulations
CL – Ceiling Exposure Limit
CWA – Clean Water Act
DOT – Department of Transportation
DSCL – Dangerous Substances Classification and Labeling (Europe)
DSL – Domestic Substance List (Canada)
EEC/EU – European Economic Community/European Union
EINECS – European Inventory of Existing Commercial Chemical Substances
HCS – Hazard Communication System
HMIS – Hazardous Material Information System
IARC – International Agency for Research on Cancer
LD50/LC50 – Lethal Dose/Concentration kill 50%
LDLo/LCLo – Lowest Published Lethal Dose/Concentration
NFPA – National Fire Prevention Association
NIOSH – National Institute for Occupational Safety & Health
NTP – National Toxicology Program
OSHA – Occupational Safety & Health Administration
PEL – Permissible Exposure Limit
RCRA – Resource Conservation and Recovery Act
SARA – Superfund Amendments and Reorganization Act
STEL – Short Term Exposure Limit (15 minutes)
TDG – Transportation of Dangerous Goods (Canada)
TLV-TWA – Threshold Limit Value-Time Weighted Average
TSCA – Toxic Substances Control Act
WHMIS – Workplace Hazardous Material Information System

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named manufacturer nor any of its subsidiaries assumes any liability whatsoever for accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

END OF MSDS DOCUMENT